

ECOPROTECT™ & ECOCLEAN™ Surface Protection Films



Films for all surfaces!

- ✓ Aluminium Composite Panels
- ✓ Stainless Steel
- ✓ Pre-Coated Metals
- ✓ Decorative Laminates
- ✓ Home & Automotive Carpets
- ✓ Aluminium & uPVC Profiles
- ✓ Marble, Stone, Quartz
- ✓ Window & Glass
- ✓ HVAC/Vent/Duct
- ✓ Plastic Sheets

75

Million
Square Meters

Surface Protection Films - Annual Capacity



Ecoplast Ltd.

1

4+ Decades of
Manufacturing
Experience

2

Public Company
- Listed on the
Bombay Stock
Exchange

3

ISO 9001,
14001, 22000
Certified

4

Start-of-the-
art Automated
Facility



Trusted and
innovative
suppliers of
Surface
Protection Films



Ecoplast Ltd.

ECOPROTECT™ Surface Protection Films for Pre-Coated Metals



@ www.ecoplastindia.com | +91- 22-66664050
info@ecoplastindia.com | +91- 22-68324115

Sales Office: 1309/1310 Hubtown Solaris, N.S. Phadke Road, Andheri E, Mumbai, Maharashtra, India - 400069

Works & Reg. Office: N.H. No. 8, Waterworks Cross Road, Abrama, Valsad, Gujarat, India - 396 002

ECOPROTECT™


Surface Protection Films

for Pre-Coated Metals


ECOPROTECT™ is a series of Surface Protection Films designed specifically for the protection of Pre-Coated Metals.

There are numerous risks of damage, scratches, and contamination throughout the production, storage, transit, and installation phases of your materials.

Our engineered protective films are tailored to preserve the integrity of your products.



Insulated Foamed Panels




Corrugated Profiles



Roof Tile Metal Sheets



PPGI/PPGL Coils



KEY FEATURES



Easy, uniform, and quiet unwinding of film rolls.



Optimal adhesive strength is rapidly achieved as soon as the film is applied on both sides.



Film does not lift or get removed during operations. It is resistant to various mechanical and thermal stresses.



Films have ideal puncture resistance, elongation, and tensile strength properties. No fibers or strains visible after cutting



Films come with UV radiation-blocking properties - protects against outdoor UV exposure of 3, 6, 9, and 12 months.



Easy, effortless, uniform, optimal peel-off strength - without tearing.



Zero risk of any residue (film or adhesive) left behind on the profile surface

PRODUCT RANGE & TECHNICAL DATA

Product	ECOPROTECT™ 203G-X	ECOPROTECT™ 204G-X
Common Thickness (mic)	50	50
Common Colour	Clear Transparent	Clear Transparent
Adhesive Type	Water Acrylic	Water Acrylic
Tensile Strength (gms/mm2) - MD	19 - 23	17 - 22
Tensile Strength (gms/mm2) - TD	17 - 19	18 - 20
Elongation (%) - MD	600 - 800	500 - 700
Elongation (%) - TD	850 - 950	750 - 950
Adhesion Value (gms/25mm)	70 - 130	100 - 160

Compatible with all coatings:

Polyester

PUR

PVDF

PVC plastisol

Designed for all End Applications



Roofing, Facades & Wall Claddings



Insulated Storage Units



Garages

Boilers

Industrial Machine Casings -
Food & Sanitary Applications